

DESIGN 300












TECHNICAL DATA SHEET

VINYL

Type of flooring **EN 653** Expanded polyvinyl chloride floor covering

Class of use **EN 685**  **class 23** **class 31** 

Description

| | | | | | | |
|---|--------|-----------------|-------------|---|-------------------|----------|
|  | EN 426 | Length | 25 m |  | Guarantee | 10 years |
|  | EN 426 | Width | 4 + 3 + 2 m |  | Surface Treatment | SUPREME |
|  | EN 428 | Total thickness | 3,0 mm |  | Mat Effect | |
|  | EN 429 | Wear layer | 0,25 mm |  | Slip Resistant | |
|  | EN 430 | Total weight | 1,85 kg/sqm | | | |










EN 14041 : 2004

Delivered by: TARKETT GLD SA
Op der Sang 2, L-9779 LENTZWEILER

| | | | | | | | |
|--|------------|----------------------------------|----------------------------------|---|----------|-----------------|----------|
|  | EN 13501-1 | Fire classification Report N° | B _{fl} -s1 RA06-0060 |  | EN 13893 | Slip resistance | ≥ 0,30 μ |
|--|------------|----------------------------------|----------------------------------|---|----------|-----------------|----------|

OPTIONAL CHARACTERISTICS

| | | | | | | | |
|--|-------------|-----------------------|-----------|---|--------------|---|--------|
|  | ISO 105/B02 | Light fastness | ≥ 6 |  | EN 1815 | Static electrical propensity | ≤ 2 kV |
|  | EN 434 | Dimensional stability | ≤ 0,4% |  | EN ISO 717/2 | Impact sound absorption | 18 dB |
|  | EN 433 | Static indentation | ≤ 0,35 mm |  | EN 12524 | Thermal resistance for underfloor heating | Ok |
|  | EN 660-1 | Abrasion group | T | | | | |