


Product  
Datasheet  
2010



WOOD

Salsa  
Bravo



WOOD

# Salsa Bravo



## TECHNICAL INFORMATION

|   | Salsa  | Bravo                |
|---|--|----------------------|
| Thickness   | 14 mm  | 14 mm                |
| Width   | 188/192  | 188                  |
| Length  | 2272/2525  | 2525                 |
| Wearlayer thickness (mm)                          | app. 3,6   | app. 3,6             |
| Weight (kg/m <sup>2</sup> )                       | app. 8,0   | app. 8,0             |
| <b>Taber Abraser/Lacquer's wear resistance*</b>   |  |                      |
| prEN 13696  |  |                      |
| abrasion penetration Proteco Lacq.(revs)          | >4000  | >4000                |
| abrasion penetration Proteco Nat.(revs)           | >3500  | >3500                |
| abrasive wear (mg/100revs)                        | app. 3,5   | app. 3,5             |
| <b>Reduction of sound weighted index</b>          |  |                      |
| <b>index "footfall" to the room below.</b>        |  |                      |
| NF EN ISO 140-8 / Acc to NF EN ISO 717-2,         |  |                      |
| ΔL <sub>w</sub> in dB with 2 mm Tarkofoam/flex II | 17   | 17                   |
| <b>Formaldehyde emission</b>                      |  |                      |
| EN 13986  | E1   | E1                   |
| <b>Reaction to Fire</b>                           |  |                      |
| EN 13501  | D <sub>fl</sub>  | D <sub>fl</sub>      |
| <b>Thermal insulation value</b>                   |  |                      |
| (RT m <sup>2</sup> K/W)                           |  |                      |
| board only  | 0,101  | 0,101                |
| with rag felt                                     | 0,121  | 0,121                |
| with 2 mm Tarkofoam/flex II                       | 0,141  | 0,141                |
| <b>Installation**</b>                             |  |                      |
|   | Floating / Glue down   | Floating / Glue Down |
| <b>Underfloor heating compatible***</b>           |  |                      |
|   | Maximum floor surface temperature 27°C with self-regulating under-floor heat system. |                      |

\* Data show results with new components according to 2006 update. Method not applicable for brushed products due to the structured surface.

\*\* Contact your flooring supplier for further information

\*\*\* Not suitable for the woodspecies beech and maple

Wood floors, Brinell Hardness (BHN), EN1534



## Salsa

| Lacquer<br>Ultra loc<br>l: 2525mm<br>w: 188mm | Natura<br>Ultra loc<br>l: 2525mm<br>w: 188mm | Lacquer<br>2-lock<br>l: 2272mm<br>w: 192mm | Natura<br>2-lock<br>l: 2272mm<br>w: 192mm | Hardwax<br>Oil<br>2-lock<br>l: 2272mm<br>w: 192mm |
|---|--|--|---|---|
|---|--|--|---|---|

### 3-strip, t: 14 mm

|                       |   |   |   |   |
|-----------------------|---|---|---|---|
| Oak Select            | • | • | • | • |
| Oak Nature            | • | • | • | • |
| Oak Nature Brushed    | • | • | • | • |
| Oak Rustical          | • | • | • | • |
| Oak Nordic White      | • | • | • | • |
| Oak Robust White      | • | • | • | • |
| Oak Cumin             | • | • | • | • |
| Oak Black Brushed     | • | • | • | • |
| Oak Silver Star       | • | • | • | • |
| Red Oak               | • | • | • | • |
| Ash Nature            | • | • | • | • |
| Ash Nature White      | • | • | • | • |
| Ash Cognac            | • | • | • | • |
| Ash Cognac Brushed    | • | • | • | • |
| Ash White Pearl       | • | • | • | • |
| Ash Purple Rain       | • | • | • | • |
| Ash Smoked            | • | • | • | • |
| Maple Canadian Nature | • | • | • | • |
| Birch                 | • | • | • | • |
| Cherry                | • | • | • | • |
| Beech Nature          | • | • | • | • |
| Beech Classic         | • | • | • | • |
| Beech Steamed         | • | • | • | • |
| Beech Maroon          | • | • | • | • |
| Walnut                | • | • | • | • |
| Merbau                | • | • | • | • |
| African Mahogany      | • | • | • | • |
| Jatoba                | • | • | • | • |
| Doussié Africana      | • | • | • | • |
| Msasa                 | • | • | • | • |
| Patina Oak White      | • | • | • | • |
| Patina Oak Black      | • | • | • | • |

### Lacquer, Tongue & Groove

### Salsa Basket Weave, 14 × 2525 × 188 mm

|                |   |
|----------------|---|
| Oak 3-strip    | • |
| Walnut 4-strip | • |

### Lacquer, 2-lock

### Salsa Fine Line, 14 × 2272 × 192 mm

|     |   |
|-----|---|
| Oak | • |
|-----|---|

## Bravo

### Lacquer Ultra loc Natura Ultra loc

### 3-strip, 14 × 2525 × 188 mm

|                       |   |   |
|-----------------------|---|---|
| Oak Robust            | • | • |
| Ash Robust            | • | • |
| Maple Canadian Robust | • | • |
| Birch Robust          | • | • |
| Cherry Robust         | • | • |
| Beech Robust          | • | • |
| Walnut                | • | • |