


Product
Datasheet
2010



WOOD
Viva
Rumba

WOOD

Viva Rumba



TECHNICAL INFORMATION


| | Viva | Rumba |
|-------------------------------------------------|--------------------------------------------------------------------------------------|---------------------|
| Thickness | 8,5 mm | 13 mm |
| Width | 110/190 | 188 |
| Length | 1220 | 1250/2525 |
| Wearlayer thickness (mm) | app. 0,6 | app. 2,5 |
| Weight (kg/m ²) | app. 8,1 | app. 7,2 |
| Taber Abraser/Lacquer's wear resistance* | | |
| prEN 13696 | | |
| abrasion penetration Proteco Lacq.(revs) | >4000 | >4000 |
| abrasion penetration Proteco Nat.(revs) | >3500 | >3500 |
| abrasive wear (mg/100revs) | app. 3,5 | app. 3,5 |
| Reduction of sound weighted index | | |
| index "footfall" to the room below. | | |
| NF EN ISO 140-8 / Acc to NF EN ISO 717-2, | | |
| ΔL_W in dB with 2 mm Tarkofoam/flex II | 17 | 17 |
| Formaldehyde emission | | |
| EN 13986 | E1 | E1 |
| Reaction to Fire | | |
| EN 13501 | C _{fl} | D _{fl} |
| Thermal insulation value | | |
| (RT m ² K/W) | | |
| board only | 0,054 | 0,101 |
| with rag felt | 0,074 | 0,121 |
| with 2 mm Tarkofoam/flex II | 0,094 | 0,141 |
| Installation** | Floating | Floating /Glue Down |
| Underfloor heating compatible*** | Maximum floor surface temperature 27°C with self-regulating under-floor heat system. | |

* Data show results with new components according to 2006 update. Method not applicable for brushed products due to the structured surface.

** Contact your flooring supplier for further information

*** Not suitable for the woodspecies beech and maple in Rumba.

Wood floors, Brinell Hardness (BHN), EN1534



Viva

| | Lacquer Ultraloc | Natura Ultraloc |
|---------------------------------------------------------------------|------------------|-----------------|
| 3-strip, 8,5 × 1220 × 190 mm | | |
| Oak | • | • |
| Maple | • | • |
| Maple Nature | • | • |
| Cherry | • | • |
| Beech | • | • |
| Beech Nature | • | • |
| Walnut | • | • |
| African Mahogany | • | • |
| 2-strip, 8,5 × 1220 × 190 mm | | |
| Oak | • | • |
| Oak Brushed | • | • |
| Oak White | • | • |
| Ash White | • | • |
| Cherry | • | • |
| Sucupira | • | • |
| Walnut | • | • |
| Ash Design White | • | • |
| Plank, 8,5 × 1220 × 190 mm. Microbevel on all four sides | | |
| Oak | • | • |
| Oak Brushed | • | • |
| Oak Brown Brushed | • | • |
| Ash Design Grey Concrete Brushed | • | • |
| Bamboo | • | • |
| Viva Contra, 8,5 × 1220 × 190 mm | | |
| Oak | • | • |
| Walnut | • | • |
| Viva Line, 8,5 × 1220 × 110 mm. Microbevel on all four sides | | |
| Oak | • | • |
| Oak Brushed | • | • |
| Cherry | • | • |
| Walnut | • | • |

Rumba

| | Lacquer Ultraloc | Natura Ultraloc |
|------------------------------------|------------------|-----------------|
| 3-strip, 13 × 2525 × 188 mm | | |
| Oak Nature | • | • |
| Oak Nature Brushed | • | • |
| Oak Milky White | • | • |
| Oak Robust | • | • |
| Ash Nature | • | • |
| Beech Nature | • | • |
| Beech Classic | • | • |
| Merbau | • | • |