










Type of flooring **EN 653** **Expanded polyvinyl chloride floor covering**

Class of use **EN 685** **class 23**  **class 31** 

Description

	EN 426	Length	30 m		Guarantee	10 years
	EN 426	Width	4+ 3 + 2 m		Surface Treatment	SUPREME
	EN 428	Total thickness	2,6 mm		Mat Effect	
	EN 429	Wear layer	0,25 mm		Slip Resistant	
	EN 430	Total weight	1,70 kg/sqm			










EN 14041 : 2004

Delivered by: TARKETT GLD SA
Op der Sang 2, L-9779 LENTZWEILER

	EN 13501-1	Fire classification Report N°	B _{fl} -s1 RA06-0060		EN 13893	Slip resistance	≥ 0,30 μ
--	------------	----------------------------------	----------------------------------	---	----------	-----------------	----------

OPTIONAL CHARACTERISTICS

	ISO 105/B02	Light fastness	≥ 6		EN 1815	Static electrical propensity	≤ 2 kV
	EN 434	Dimensional stability	≤ 0,4%		EN ISO 717/2	Impact sound absorption	19 dB
	EN 433	Static indentation	≤ 0,35 mm		EN 12524	Thermal resistance for underfloor heating	Ok
	EN 660-1	Abrasion group	T				